


TECHNICAL DATA SHEET



Type no.		P95 05
Article no.		013595050101
Standards		DIN EN 50342-1, 50342-2
Application		Starter battery
Electrical data		
Rated voltage		12V
Rated capacity		95 Ah (K20)
Cold start current		740 A (EN)
Dimensions and weights		
Box	D31/56AT	
Length max.	303mm	
Width max.	173mm	
Box height max.	203mm	
Total height max.	225mm	
Battery weight	Ca. 21,5 kg (+/- 5 %)	
Electrolyte density		Approx. 1,28 kg/l
Electrolyte		Diluted sulphuric acid
Items/pallet		42
Pallet ID		Euro pallet
Items per layer		14
Features		
Base hold-down		B07
Layout		1
Terminal		1
Separator		PE envelope separator
Degassing		Battery with central degassing
Flame arrester		Integrated
Performance identification		W4 - C2 - V2 - E1
Maintenance ¹⁾		
Water consumption		W4
Refill water		Distilled or demineralised (DIN 43530)
Self-discharge		Approx. 3 % per month
Charging current		Approx. 1/10 of the rated capacity
Charging voltage ²⁾		max. 14,8 V



¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2018-04-01 ; Rights relating to changes and errors retained.
original