THE POWER COMPANY

TECHNICAL DATA SHEET

Banner
THE POWER COMPANY

Type no.	544 09

Article no.	010544090101
Standards	DIN EN 50342-1, 50342-2
Application	Starter battery

Electrical data	
Rated voltage	12V
Rated capacity	44 Ah (K20)
Cold start current	360 A (EN)

Dimensions and weights		
Box	T4	
Length max.	210mm	
Width max.	175mm	
Box height max.	175mm	
Total height max.	175mm	
Battery weight	Ca. 11,5 kg (+/- 5 %)	
Electrolyte density		Approx. 1,28 kg/l
Electrolyte		Diluted sulphuric acid
Items/pallet		88
Pallet ID		Euro pallet
Items per layer		22

Features	
Base hold-down	B13
Layout	0
Terminal	1
Separator	PE bag separator
Degassing	Battery with central degassing
Flame arrester	Integrated
Performance identification	W4 - C2 - V1 - E1

Maintenance [1])	
Water consumption	W4
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage [2])	max. 14,8 V

[1]) All the listed values relate to room temperature +25° C
[2]) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2018-04-01 ; Rights relating to changes and errors retained.
original

Banner GmbH, A-4021 Linz, Banner Straße 1
Tel. +43(0) 732/38 88-0, e-mail: internet@bannerbatterien.com

LEADING COMPANIES OF AUSTRIA