

TECHNICAL DATA SHEET



Type no.	560 10
Article no.	010560100101
Standards	DIN EN 50342-1, 50342-2
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	60 Ah (K20)
Cold start current	675 A (EN)
Dimensions and weights	
Box	
Length max.	248mm
Width max.	178mm
Box height max.	184mm
Total height max.	184mm
Battery weight	Ca. 15,5 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	72
Pallet ID	Euro pallet
Items per layer	16
Features	
Base hold-down	B07
Layout	1
Terminal	5
Separator	PE bag separator
Degassing	Battery with central degassing
Flame arrester	Not integrated
Performance identification	W4 - C2 - V1 - E1
Maintenance ¹⁾	
Water consumption	W4
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 14,8 V

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2018-04-01 ; Rights relating to changes and errors retained.
original