THE POWER COMPANY

TECHNICAL DATA SHEET

Banner
THE POWER COMPANY

Type no.	570 44

Article no.	010570440101
Standards	DIN EN 50342-1, 50342-2
Application	Starter battery

Electrical data	
Rated voltage	12V
Rated capacity	70 Ah (K20)
Cold start current	640 A (EN)

Dimensions and weights		
Box	T6	
Length max.	278mm	
Width max.	175mm	
Box height max.	175mm	
Total height max.	175mm	
Battery weight	Ca. 17,0 kg (+/- 5 %)	
Electrolyte density		Approx. 1,28 kg/l
Electrolyte		Diluted sulphuric acid
Items/pallet		64
Pallet ID		Euro pallet
Items per layer		16

Features	
Base hold-down	B13
Layout	0
Terminal	1
Separator	PE bag separator
Degassing	Battery with central degassing
Flame arrester	Integrated
Performance identification	W4 - C2 - V1 - E1

Maintenance [1])	
Water consumption	W4
Refill water	Destilliert oder entmineralisiert (DIN 43530)
Self-discharge	Ca. 3 % pro Monat
Charging current	Ca. 1/10 der Nennkapazität
Charging voltage [2])	max. 14,8 V

[1]) All the listed values relate to room temperature +25° C
[2]) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2018-04-01 ; Rights relating to changes and errors retained. original

Banner GmbH, A-4021 Linz, Banner Straße 1
Tel. +43(0) 732/38 88-0, e-mail: internet@bannerbatterien.com
LEADING COMPANIES OF AUSTRIA